



Image	Servex Part #	Model	SRP RM	Resolution	Brightness (Ansi Lumen)	Contrast Ratio	Lamp Life (Hrs)	Throw Ratio	Zoom Ratio	Keystone	Interface	Weight	Speaker	Cable Included	Carry Case	Features	Remarks	
Retail Models : Value Series / F & B / Meeting Rooms																		
	5M.PJB00.055	MS550	1,399	SVGA (800 X 600)	3600	20000 : 1	Lamp Save 15,000	1.96~2.15	1.1X	Vertical: ± 40 degrees	PC (D-sub) x1 Monitor out (D-sub 15pin) x1 S-Video in (Mini DIN 4pin) x1 Composite Vide in (RCA) x1 HDMI x2, USB Type Mini B x1 Audio in x1, Audio out x1 RS232 (DB-9pin) x1 IR Receiver x1, Security Bar x1	2.3kg	2W x 1	VGA	Yes (S)	 	One-Touch Access to Install Functions	
	5M.PJB00.056	MX550	1,699	XGA (1024 X 768)	3600	20000 : 1	Lamp Save 15,000	1.96~2.15	1.1X	Vertical: ± 40 degrees		2.3kg	2W x 1	VGA	Yes (S)	 	One-Touch Access to Install Functions	
	5M.PJB00.064	MW550	1,999	WXGA (1280 X 800)	3600	20000 : 1	Lamp Save 15,000	1.55~1.7	1.1X	Vertical: ± 40 degrees		2.3kg	2W x 1	VGA	Yes (S)	 	One-Touch Access to Install Functions	
	5M.PJB00.071	MH550	2,729	1080p (1920 X 1080)	3500	20000 : 1	Lamp Save 15,000	1.49~1.64	1.1X	Vertical: ± 40 degrees		2.3kg	2W x 1	VGA	Yes (S)	 	One-Touch Access to Install Functions	
	5M.PJB00.053	MX611	2,369	XGA (1024 X 768)	4000	20000 : 1	Lamp Save 15,000	1.96-2.15	1.1:1	ID, Vertical +/- 30 degrees		2.3kg	2W x 1	VGA	Yes (S)	 	Wireless Presentation Capability	
	5M.PJB00.057	MW612	2,729	WXGA (1280 X 800)	4000	20000 : 1	Lamp Save 15,000	1.55-1.7	1.1:1	ID, Vertical +/- 30 degrees	2.3kg	2W x 1	VGA	Yes (S)	 	Wireless Presentation Capability		
Short Throw Models with USB Port : F & B / Meeting Rooms																		
	5M.PJB00.021	MX631ST	2,539	XGA (1024 X 768)	3200	13000 : 1	SmartEco 10,000	0.9~1.08	1.2X	ID, Auto Vertical +/- 30 degrees	PC (D-sub) x1 Monitor out (D-sub 15pin) x1 S-Video in (Mini DIN 4pin) x1 Composite Vide in (RCA) x1 HDMI x2, USB Type A x1, USB Type Mini B x1 Audio in x1, Audio L/R in (RCA) x1, Audio out x1 RS232 (DB-9pin) x1 IR Receiver x2, Security Bar x1	2.6kg	10W x1	VGA	Yes (B)	 	Wireless Presentation Capability	
	5M.PJB00.059	MW826ST	2,999	WXGA (1280 x 800)	3400	20,000 : 1	LampSave 15000	0.49	Fixed	ID; Vertical ± 30 degrees	PC (D-sub) x2 Monitor out (D-sub 15pin) x1 S-Video in (Mini DIN 4pin) x1 Composite Vide in (RCA) x1 HDMI x2, USB Type A x1, USB Type Mini B x1 Audio in x1, Audio L/R in (RCA) x1, Audio out x1, Lan RJ45 x1 RS232 (DB-9pin) x1 IR Receiver x2	2.6kg	10W x 1	VGA	Yes (B)	 	-Anti-Dust Accumulation Sensor Resists Dust Buildup - Expanding Classroom Possibilities with Short Throw Ratio - Centralized Multiple Display Management	

*SmartEco
 *LampSave

By detecting the input content to determine the amount of brightness required for optimum color and contrast performance, the SmartEco Mode is able to reduce lamp power while delivering the finest image quality. No compromise!
 Less lamp replacements and maintenance translates into an overall lower cost of ownership. The LampSaveMode does exactly that by adjusting the lamp power dynamically by content level to extend projector lamp life significantly by up to 50% as compared to normal mode.